

HYDROLOGICAL CALCULATION RATIONAL METHOD (HP # 5 - 1989)

PROJECT : catchment 5 (Existing)
Tabung Haji, Pahang

A. CATCHMENT CHARACTERISTICS

From Topo Map sheets :
Area of catchment, A_c = 76.63 sq. km
Length of mainstream, L = 19.39 km
Percentage developed, = 0.00 % (Land use factor)

Weighted mean slope, s

l_i (km)	h_i (m)	$s_i = h_i / l_i$ (%)	$l_i \cdot \sqrt{s_i}$
8.77	60.00	0.68	7.25
4.30	200.00	4.65	9.27
6.32	100.00	1.58	7.95
19.39	360.00	6.92	24.48

$$s = \frac{\sum (l_i \cdot \sqrt{s_i})}{\sum l_i} = \frac{24.48}{19.39} = 1.59 \%$$

B. LOCATION OF BRIDGE

From Topo Sheet No :

Longitude 102° 18' 0" E
Latitude 4° 12' 0" N

From figure 1 of HP # 5
Region No 4

Note : Region 1 - Perlis, Kedah, Perak
Region 2 - Kuala Lumpur
Region 3 - Johor
Region 4 - Kelantan, Terengganu, Pahang

C. ESTIMATION OF THE DESIGN RAINSTORM

1. Adopt return period, T = 2 years (HP # 1)

$$T_c = \frac{1.286 \times L}{\{A^{0.223} \times S^{0.263}\}} = \frac{1.286 \times 19.39}{\{76.63^{0.223} \times 1.593587313^{0.263}\}} = 8.38 \text{ hours} = 502.95 \text{ mins}$$

3. Values of $x(T, t)$
(N.B. values of t is to envelope the value of T_c)

From Fig. 1 to 8 of HP # 1 :

$x(2, 3) = 40$ mm
 $x(20, 3) = 70$ mm
 $x(2, 24) = 80$ mm
 $x(20, 24) = 140$ mm

4. Plot those values above on graph Figure 10 of HP # 1

5. Read off values, with $T = 2$ years.

$x(T, 3) = 75.00$ mm
 $x(T, 24) = 120.00$ mm

6. Plot values obtained in steps 3 and 5 on graph Fig. 9 of HP # 1.

7. Read off values :

With $T_c = 8.38$ hours and $T = 2$ years.
 $x(2, 8.38) = 59.77$ mm
 $x(20, 8.38) = 104.59$ mm
 $x(T, 8.38) = 97.24$ mm

8. Confidence limits

$$D = x(20) - x(2) = 104.58971 - 44.824162 = 59.765549$$

$$0.43 D = 19.27439 \text{ mm}$$

$$\begin{aligned} \text{Max } x(T) &= x(T) + 0.43 D \\ &= 97.236243 + 19.27439 \\ &= 116.51 \text{ mm} \end{aligned}$$

D. FLOOD ESTIMATION

1. From step C,

$$\begin{aligned} \text{Max } x_i(2) &= 116.51063 \text{ mm} \\ \text{Therefore, } i(2) &= x(100) = 116.51063 \end{aligned}$$

$$2. \text{ From Figure 4 with, } T_c = 13.90 \text{ mm/hr} = 8.3824889$$

$$\text{Region} = 4$$

$$T = 2 \text{ years.}$$

$$C_{10} = 0.38$$

$$C_t / C_{10} = 0.712$$

$$\text{Therefore } C_t = 0.27$$

$$3. \text{ Percentage developed} = 0\%$$

$$\text{Land use factor, } F = 1$$

THEREFORE

$$Q_{\max} = F \times 0.278 \times C_t \times i(T) \times A$$

$$= 80.11 \text{ cu. m/s}$$

E. DETERMINATION OF THE FLOOD WATER LEVEL AND VELOCITY

1. Plot cross-section of the river.
2. consider the recorded flood level as our first trial
3. Divide into sub-section
4. Stream slope at bridge site,

From the river survey plan :

Number of Part	= 4 Section			
Part	BedL1	BedL2	Length	Slope
1	6.880	6.544	60.000	0.006
2	6.544	6.067	25.000	0.019
3	6.067	6.037	25.000	0.001
4	6.037	5.604	20.000	0.022
5				
6				
7				
Average Slope, S _o	0.0118825			

5. Calculation of V_m and Q_c

$$V_i = R_i^{(2/3)} \times S_o^{(1/2)} / n_i$$

$$\text{TRY Flood Level} = 7.700 \text{ m} \quad \text{OK}$$

Sc.	Level	Chng.	Roughness	Area, A	Wetted	Hydraulic	Velocity	Q=V _i A _i
	(m)	(m)	n _i	Sq. ft	perimeter	Radius	(m/s)	(cu. m)
					(pi) (m)	R _i = A _i / P _i		
						(m)		
0	9.200	0.000	0.045					
1	7.000	4.000	0.045	-1.600	4.565	-0.350	#NUM	
2	6.741	18.000	0.045	11.613	14.002	0.829	2.138	24.832
3	5.857	23.100	0.045	7.145	5.176	1.380	3.003	21.458
4	5.792	27.000	0.045	7.314	3.901	1.875	3.684	26.944
5	5.272	33.600	0.045	14.309	6.620	2.161	4.049	57.941
6	6.344	38.000	0.045	8.325	4.529	1.838	3.635	30.261
7	6.659	42.500	0.045	5.393	4.511	1.196	2.729	14.717
8	7.000	50.500	0.045	6.964	8.007	0.870	2.207	15.370
9	9.200	54.000	0.045					
10								
			TOTAL	59.4634			TOTAL	191.52328

Type of bed material (Code) = 7 Rock

Therefore,

$$\text{Mean velocity, } V_m = \frac{E(V_i A_i)}{E(A_i)}$$

$$= \frac{191.523277}{59.4634}$$

$$= 3.220859839 < 5.18 \text{ m/sec}$$

Therefore OK

$$\text{Discharge capacity, } Q_c = \frac{V_m \times E(A_i)}{191.523277}$$

$$= 80.1124 \text{ cu. m}$$

Therefore OK

CODE	BED
1	Clay
2	Sandy Clay
3	Very fine sand
4	Fine sand
5	Fine Gravel
6	Rocky soil
7	Rock
8	Grass-lined

5.1 HP5 catchment 5 Tabung Haji (Existing)

HYDROLOGICAL CALCULATION RATIONAL METHOD (HP # 5 - 1989)

PROJECT : catchment 5 (Existing)
Tabung Haji, Pahang

A. CATCHMENT CHARACTERISTICS

From Topo Map sheets :

Area of catchment, A_c = 76.63 sq. km
Length of mainstream, L = 19.39 km
Percentage developed, = 0.00 % (Land use factor)

Weighted mean slope, s

l_i (km)	h_i (m)	$s_i = h_i / l_i$ (%)	$l_i * \text{SQRT } s_i$
8.77	60.00	0.68	7.25
4.30	200.00	4.65	9.27
6.32	100.00	1.58	7.95
19.39	360.00	6.92	24.48

$$s = \frac{\sum (l_i * \text{SQRT } s_i)}{\sum l_i}$$

$$= \frac{24.48}{19.39}$$

$$= 1.59 \%$$

B. LOCATION OF BRIDGE

From Topo Sheet No :

Longitude 102° 18' 0" E
Latitude 4° 12' 0" N

From figure 1 of HP # 5
Region No 4

Note : Region 1 - Perlis, Kedah, Perak
Region 2 - Kuala Lumpur
Region 3 - Johor
Region 4 - Kelantan, Terengganu, Pahang

C. ESTIMATION OF THE DESIGN RAINSTORM

1. Adopt return period, T = 5 years (HP # 1)

$$T_c = \frac{1.286 \times L}{\{A^{0.223} \times S^{0.263}\}}$$

$$= \frac{1.286 \times 19.39}{\{76.63^{0.223} \times 1.593587313^{0.263}\}}$$

$$= 8.38 \text{ hours}$$

$$= 502.95 \text{ mins}$$

3. Values of $x(T, t)$
(N.B. values of t is to envelope the value of T_c)

From Fig. 1 to 8 of HP # 1 :

$x(2, 3)$ = 40 mm
 $x(20, 3)$ = 70 mm
 $x(2, 24)$ = 80 mm
 $x(20, 24)$ = 140 mm

4. Plot those values above on graph Figure 10 of HP # 1

5. Read off values, with T = 5 years.

$x(T, 3)$ = 98.94 mm
 $x(T, 24)$ = 176.59 mm

6. Plot values obtained in steps 3 and 5 on graph Fig. 9 of HP # 1.

7. Read off values :

5.1 HP5 cat chment 5 Tabung Haji (Q exi st i ng)

$$\begin{aligned}
 & \text{With } T_c = 8.3824889 \text{ hours} \\
 & \text{and } T = 5 \text{ years.} \\
 & x(2, 8.38) = 59.77 \text{ mm} \\
 & x(20, 8.38) = 104.59 \text{ mm} \\
 & x(T, 8.38) = 137.31 \text{ mm}
 \end{aligned}$$

8. Confidence limits

$$\begin{aligned}
 D &= x(20) - x(2) \\
 &= 104.58971 - 59.765549 \\
 &= 44.824162 \\
 0.43 D &= 19.27 \text{ mm}
 \end{aligned}$$

$$\begin{aligned}
 9. \text{ Max } x(5) &= x(T) + 0.43 D \\
 [T = 5] &= 137.3117 + 19.27439 \\
 &= 156.59 \text{ mm}
 \end{aligned}$$

D. FLOOD ESTIMATION

1. From step C,

$$\begin{aligned}
 \text{Max } x(5) &= 156.58609 \text{ mm} \\
 \text{Therefore, } i(10) &= x(100) = 156.58609 \\
 &= \frac{T_c}{8.3824889} \\
 &= 18.68 \text{ mm / hr}
 \end{aligned}$$

2. From Figure 4 with,

$$\begin{aligned}
 \text{Region} &= 4 \\
 T &= 5 \text{ years.} \\
 C_{10} &= 0.38 \\
 C_t / C_{10} &= 0.88 \\
 \text{Therefore } C_t &= 0.3344
 \end{aligned}$$

$$\begin{aligned}
 3. \text{ Percentage developed} &= 0 \% \\
 \text{Land use factor, } F &= 1
 \end{aligned}$$

THEREFORE

$$\begin{aligned}
 Q_{\max} &= F \times 0.278 \times C_t \times i(T) \times A \\
 &= 133.07 \text{ cu. m / s}
 \end{aligned}$$

5.1 HP5 catchment 5 Tabung Haji (Q existing)

HYDROLOGICAL CALCULATION RATIONAL METHOD (HP # 5 - 1989)

PROJECT : catchment 5 (Existing)
Tabung Haji, Pahang

A. CATCHMENT CHARACTERISTICS

From Topo Map sheets :

Area of catchment, A_c = 76.63 sq. km
Length of mainstream, L = 19.39 km
Percentage developed, = 0.00 % (Land use factor)

Weighted mean slope, s

l_i (km)	h_i (m)	$s_i = h_i / l_i$ (%)	$l_i * \text{SQRT } s_i$
8.77	60.00	0.68	7.25
4.30	200.00	4.65	9.27
6.32	100.00	1.58	7.95
19.39	360.00	6.92	24.48

$$s = \frac{\sum (l_i * \text{SQRT } s_i)}{\sum l_i}$$

$$= \frac{24.48}{19.39}$$

$$= 1.59 \%$$

B. LOCATION OF BRIDGE

From Topo Sheet No :

Longitude 102° 18' 0" E
Latitude 4° 12' 0" N

From figure 1 of HP # 5
Region No 4

Note : Region 1 - Perlis, Kedah, Perak
Region 2 - Kuala Lumpur
Region 3 - Johor
Region 4 - Kelantan, Terengganu, Pahang

C. ESTIMATION OF THE DESIGN RAINSTORM

1. Adopt return period, T = 10 years (HP # 1)

$$T_c = \frac{1.286 \times L}{\{A^{0.223} \times S^{0.263}\}}$$

$$= \frac{1.286 \times 19.39}{\{76.63^{0.223} \times 1.593587313^{0.263}\}}$$

$$= 8.38 \text{ hours}$$

$$= 502.95 \text{ mins}$$

3. Values of $x(T, t)$
(N.B. values of t is to envelope the value of T_c)

From Fig. 1 to 8 of HP # 1 :

$x(2, 3)$ = 40 mm
 $x(20, 3)$ = 70 mm
 $x(2, 24)$ = 80 mm
 $x(20, 24)$ = 140 mm

4. Plot those values above on graph Figure 10 of HP # 1

5. Read off values, with T = 10 years.

$x(T, 3)$ = 114.79 mm
 $x(T, 24)$ = 214.06 mm

6. Plot values obtained in steps 3 and 5 on graph Fig. 9 of HP # 1.

7. Read off values :

5.1 HP5 cat chment 5 Tabung Haji (Q existing)

$$\begin{aligned}
 & \text{With } T_c = 8.3824889 \text{ hours} \\
 & \text{and } T = 10 \text{ years.} \\
 & x(2, 8.38) = 59.77 \text{ mm} \\
 & x(20, 8.38) = 104.59 \text{ mm} \\
 & x(T, 8.38) = 163.85 \text{ mm}
 \end{aligned}$$

8. Confidence limits

$$\begin{aligned}
 D &= x(20) - x(2) \\
 &= 104.58971 - 59.765549 \\
 &= 44.824162 \\
 0.43 D &= 19.27 \text{ mm}
 \end{aligned}$$

$$\begin{aligned}
 9. \text{ Max } x \left[\begin{matrix} x & 10 \\ T = & 10 \end{matrix} \right] &= x(T) + 0.43 D \\
 &= 163.84514 + 19.27439 \\
 &= 183.12 \text{ mm}
 \end{aligned}$$

D. FLOOD ESTIMATION

1. From step C,

$$\begin{aligned}
 \text{Max } x \left(\begin{matrix} 10 \\ \text{Therefore, } i(10) \end{matrix} \right) &= 183.11953 \text{ mm} \\
 &= x(100) = 183.11953 \\
 &= \frac{T_c}{8.3824889} \\
 &= 21.85 \text{ mm/hr}
 \end{aligned}$$

2. From Figure 4 with,

$$\begin{aligned}
 \text{Region} &= 4 \\
 T &= 10 \text{ years.} \\
 C_{10} &= 0.38 \\
 C_t / C_{10} &= 1 \\
 \text{Therefore } C_t &= 0.38
 \end{aligned}$$

$$\begin{aligned}
 3. \text{ Percentage developed} &= 0 \% \\
 \text{Land use factor, } F &= 1
 \end{aligned}$$

THEREFORE

$$\begin{aligned}
 Q_{\max} &= F \times 0.278 \times C_t \times i(T) \times A \\
 &= 176.84 \text{ cu. m/s}
 \end{aligned}$$

5.1 HP5 catchment 5 Tabung Haji (Existing)

HYDROLOGICAL CALCULATION RATIONAL METHOD (HP # 5 - 1989)

PROJECT : catchment 5 (Existing)
Tabung Haji, Pahang

A. CATCHMENT CHARACTERISTICS

From Topo Map sheets :

Area of catchment, A_c = 76.63 sq. km
Length of mainstream, L = 19.39 km
Percentage developed, = 0.00 % (Land use factor)

Weighted mean slope, s

l_i (km)	h_i (m)	$s_i = h_i / l_i$ (%)	$l_i * \text{SQRT } s_i$
8.77	60.00	0.68	7.25
4.30	200.00	4.65	9.27
6.32	100.00	1.58	7.95
19.39	360.00	6.92	24.48

$$s = \frac{\sum (l_i * \text{SQRT } s_i)}{\sum l_i}$$

$$= \frac{24.48}{19.39}$$

$$= 1.59 \%$$

B. LOCATION OF BRIDGE

From Topo Sheet No :

Longitude 102° 18' 0" E
Latitude 4° 12' 0" N

From figure 1 of HP # 5
Region No 4

Note : Region 1 - Perlis, Kedah, Perak
Region 2 - Kuala Lumpur
Region 3 - Johor
Region 4 - Kelantan, Terengganu, Pahang

C. ESTIMATION OF THE DESIGN RAINSTORM

1. Adopt return period, T = 20 years (HP # 1)

$$T_c = \frac{1.286 \times L}{\{A^{0.223} \times S^{0.263}\}}$$

$$= \frac{1.286 \times 19.39}{\{76.63^{0.223} \times 1.593587313^{0.263}\}}$$

$$= 8.38 \text{ hours}$$

$$= 502.95 \text{ mins}$$

3. Values of $x(T, t)$
(N.B. values of t is to envelope the value of T_c)

From Fig. 1 to 8 of HP # 1 :

$x(2, 3)$ = 40 mm
 $x(20, 3)$ = 70 mm
 $x(2, 24)$ = 80 mm
 $x(20, 24)$ = 140 mm

4. Plot those values above on graph Figure 10 of HP # 1

5. Read off values, with T = 20 years.

$x(T, 3)$ = 130.00 mm
 $x(T, 24)$ = 250.00 mm

6. Plot values obtained in steps 3 and 5 on graph Fig. 9 of HP # 1.

7. Read off values :

5.1 HP5 cat chment 5 Tabung Haji (Q exi st i ng)

$$\begin{aligned}
 & \text{With } T_c = 8.3824889 \text{ hours} \\
 & \text{and } T = 20 \text{ years.} \\
 & x(2, 8.38) = 59.77 \text{ mm} \\
 & x(20, 8.38) = 104.59 \text{ mm} \\
 & x(T, 8.38) = 189.30 \text{ mm}
 \end{aligned}$$

8. Confidence limits

$$\begin{aligned}
 D &= x(20) - x(2) \\
 &= 104.58971 - 59.765549 \\
 &= 44.824162 \\
 0.43 D &= 19.27 \text{ mm}
 \end{aligned}$$

$$\begin{aligned}
 9. \text{ Max } x(20) &= x(T) + 0.43 D \\
 [T = 20] &= 189.29665 + 19.27439 \\
 &= 208.57 \text{ mm}
 \end{aligned}$$

D. FLOOD ESTIMATION

1. From step C,

$$\begin{aligned}
 \text{Max } x(20) &= 208.57104 \text{ mm} \\
 \text{Therefore, } i(20) &= \frac{x(100)}{T_c} = \frac{208.57104}{8.3824889} \\
 &= 24.88 \text{ mm/hr}
 \end{aligned}$$

2. From Figure 4 with,

$$\begin{aligned}
 \text{Region} &= 4 \\
 T &= 20 \text{ years.} \\
 C_{10} &= 0.38 \\
 C_t / C_{10} &= 1.128 \\
 \text{Therefore } C_t &= 0.43
 \end{aligned}$$

$$\begin{aligned}
 3. \text{ Percentage developed} &= 0\% \\
 \text{Land use factor, } F &= 1
 \end{aligned}$$

THEREFORE

$$\begin{aligned}
 Q_{\max} &= F \times 0.278 \times C_t \times i(T) \times A \\
 &= 227.20 \text{ cu. m/s}
 \end{aligned}$$

5.1 HP5 catchment 5 Tabung Haji (Existing)

HYDROLOGICAL CALCULATION RATIONAL METHOD (HP # 5 - 1989)

PROJECT : catchment 5 (Existing)
Tabung Haji, Pahang

A. CATCHMENT CHARACTERISTICS

From Topo Map sheets :

Area of catchment, A_c = 76.63 sq. km
Length of mainstream, L = 19.39 km
Percentage developed, = 0 % (Land use factor)

Weighted mean slope, s

l_i (km)	h_i (m)	$s_i = h_i / l_i$ (%)	$l_i * \text{SQRT } s_i$
8.77	60.00	0.68	7.25
4.30	200.00	4.65	9.27
6.32	100.00	1.58	7.95
19.39	360.00	6.92	24.48

$$s = \frac{\sum (l_i * \text{SQRT } s_i)}{\sum l_i}$$

$$= \frac{24.48}{19.39}$$

$$= 1.59 \%$$

B. LOCATION OF BRIDGE

From Topo Sheet No :

Longitude 102° 18' 0" E
Latitude 4° 12' 0" N

From figure 1 of HP # 5
Region No 4

Note : Region 1 - Perlis, Kedah, Perak
Region 2 - Kuala Lumpur
Region 3 - Johor
Region 4 - Kelantan, Terengganu, Pahang

C. ESTIMATION OF THE DESIGN RAINSTORM

1. Adopt return period, T = 50 years (HP # 1)

$$T_c = \frac{1.286 \times L}{\{A^{0.223} \times S^{0.263}\}}$$

$$= \frac{1.286 \times 19.39}{\{76.63^{0.223} \times 1.593587313^{0.263}\}}$$

$$= 8.38 \text{ hours}$$

$$= 502.95 \text{ mins}$$

3. Values of $x(T, t)$
(N.B. values of t is to envelope the value of T_c)

From Fig. 1 to 8 of HP # 1 :

$x(2, 3) = 40 \text{ mm}$
 $x(20, 3) = 70 \text{ mm}$
 $x(2, 24) = 80 \text{ mm}$
 $x(20, 24) = 140 \text{ mm}$

4. Plot those values above on graph Figure 10 of HP # 1

5. Read off values, with $T = 50$ years.

$x(T, 3) = 149.68 \text{ mm}$
 $x(T, 24) = 296.52 \text{ mm}$

6. Plot values obtained in steps 3 and 5 on graph Fig. 9 of HP # 1.

7. Read off values :

5.1 HP5 cat chment 5 Tabung Haji (Q exi st i ng)

$$\begin{aligned}
 & \text{With } T_c = 8.3824889 \text{ hours} \\
 & \text{and } T = 50 \text{ years.} \\
 & x(2, 8.38) = 59.77 \text{ mm} \\
 & x(20, 8.38) = 104.59 \text{ mm} \\
 & x(T, 8.38) = 222.24 \text{ mm}
 \end{aligned}$$

8. Confidence limits

$$\begin{aligned}
 D &= x(20) - x(2) \\
 &= 104.58971 - 59.765549 \\
 &= 44.824162 \\
 0.43 D &= 19.27439 \text{ mm}
 \end{aligned}$$

$$\begin{aligned}
 9. \text{ Max } x \left[T = 50 \right] &= x(T) + 0.43 D \\
 &= 222.24102 + 19.27439 \\
 &= 241.52 \text{ mm}
 \end{aligned}$$

D. FLOOD ESTIMATION

1. From step C,

$$\begin{aligned}
 \text{Max } x(50) &= 241.51541 \text{ mm} \\
 \text{Therefore, } i(50) &= \frac{x(100)}{T_c} = \frac{241.51541}{8.3824889} \\
 &= 28.81 \text{ mm/hr}
 \end{aligned}$$

2. From Figure 4 with,

$$\begin{aligned}
 \text{Region} &= 4 \\
 T &= 50 \text{ years.} \\
 C_{10} &= 0.38 \\
 C_t / C_{10} &= 1.296 \\
 \text{Therefore } C_t &= 0.49
 \end{aligned}$$

$$\begin{aligned}
 3. \text{ Percentage developed} &= 0 \% \\
 \text{Land use factor, } F &= 1
 \end{aligned}$$

THEREFORE

$$\begin{aligned}
 Q_{\max} &= F \times 0.278 \times C_t \times i(T) \times A \\
 &= 302.28 \text{ cu. m/s}
 \end{aligned}$$

5.1 HP5 catchment 5 Tabung Haji (Q existing)

HYDROLOGICAL CALCULATION RATIONAL METHOD (HP # 5 - 1989)

PROJECT : catchment 5 (Existing)
Tabung Haji, Pahang

A. CATCHMENT CHARACTERISTICS

From Topo Map sheets :

Area of catchment, A_c = 76.63 sq. km
Length of mainstream, L = 19.39 km
Percentage developed, = 0 % (Land use factor)

Weighted mean slope, s

l_i (km)	h_i (m)	$s_i = h_i / l_i$ (%)	$l_i * \text{SQRT } s_i$
8.77	60.00	0.68	7.25
4.30	200.00	4.65	9.27
6.32	100.00	1.58	7.95
19.39	360.00	6.92	24.48

$$s = \frac{\sum (l_i * \text{SQRT } s_i)}{\sum l_i}$$

$$= \frac{24.48}{19.39}$$

$$= 1.59 \%$$

B. LOCATION OF SITE

From Topo Sheet No :

Longitude 102° 18' 0" E
Latitude 4° 12' 0" N

From figure 1 of HP # 5
Region No 4

Note : Region 1 - Perlis, Kedah, Perak
Region 2 - Kuala Lumpur
Region 3 - Johor
Region 4 - Kelantan, Terengganu, Pahang

C. ESTIMATION OF THE DESIGN RAINSTORM

1. Adopt return period, T = 100 years (HP # 1)

$$T_c = \{1.286 \times L\} / \{A^{0.223} \times S^{0.263}\}$$

$$= \frac{\{1.286 \times 19.39\}}{\{76.63^{0.223} \times 1.593587313^{0.263}\}}$$

$$= 8.38 \text{ hours}$$

$$= 502.95 \text{ mins}$$

3. Values of $x(T, t)$
(N.B. values of t is to envelope the value of T_c)

From Fig. 1 to 8 of HP # 1 :

$x(2, 3)$ = 40 mm
 $x(20, 3)$ = 70 mm
 $x(2, 24)$ = 80 mm
 $x(20, 24)$ = 140 mm

4. Plot those values above on graph Figure 10 of HP # 1

5. Read off values, with T = 100 years.

$x(T, 3)$ = 164.43 mm
 $x(T, 24)$ = 331.38 mm

6. Plot values obtained in steps 3 and 5 on graph Fig. 9 of HP # 1.

7. Read off values :

5.1 HP5 cat chment 5 Tabung Haji (Q exi sti ng)

$$\begin{aligned}
 & \text{With } T_c = 8.38 \text{ hours} \\
 & \text{and } T = 100 \text{ years.} \\
 & x(2, 8.38) = 59.77 \text{ mm} \\
 & x(20, 8.38) = 104.59 \text{ mm} \\
 & x(T, 8.38) = 246.93 \text{ mm}
 \end{aligned}$$

8. Confidence limits

$$\begin{aligned}
 D &= x(20) - x(2) \\
 &= 104.58971 - 59.765549 \\
 &= 44.824162 \\
 0.43 D &= 19.27 \text{ mm}
 \end{aligned}$$

$$\begin{aligned}
 9. \text{ Max } x &= x(T) + 0.43 D \\
 [T = 100] &= 246.92819 + 19.27439 \\
 &= 266.20 \text{ mm}
 \end{aligned}$$

D. FLOOD ESTIMATION

1. From step C,

$$\begin{aligned}
 \text{Max } x &= 266.20 \text{ mm} \\
 \text{Therefore, } i(100) &= \frac{x(100)}{T_c} = \frac{266.20258}{8.3824889} \\
 &= 31.76 \text{ mm / hr}
 \end{aligned}$$

2. From Figure 4 with,

$$\begin{aligned}
 \text{Region} &= 4 \\
 T &= 100 \text{ years.} \\
 C_{10} &= 0.38 \\
 C_t / C_{10} &= 1.46 \\
 \text{Therefore } C_t &= 0.5548
 \end{aligned}$$

$$\begin{aligned}
 3. \text{ Percentage developed} &= 0 \% \\
 \text{Land use factor, } F &= 1
 \end{aligned}$$

THEREFORE

$$\begin{aligned}
 Q_{\max} &= F \times 0.278 \times C_t \times i(T) \times A \\
 &= 375.34 \text{ cu. m /s}
 \end{aligned}$$