

Index

- abattoir: 392
- absorption: 292
- acclimatized culture: 89-90
- activated alumina: 313
- activated carbon: 295,300,302,353
- activated sludge process: 22,44-45,51-52,81,85,236
- active biomass: 156-157,
- activity coefficient: 262-264
- adsorption: 295,300,305,320,328
- aerated lagoons: 248-251
- aeration tank volume: 238
- aerator: 245
- air stripping: 261-194, see also stripping
- alkalinity: 88-90
- amino acids: 16-18,299
- ammonia load: 61
- ammonium: 8,17,19-21,23-24,35,43,55-57,66-68,81,88,92,105,110,114,154,181-184,209,216,246,255,261-266,291-293,298-302,314-322,332,353-372,392
- anilines: 110
- aquaculture: 335
- arsenic: 116,118
- assimilatory reduction: 124
- attached growth: 22,27,43-45,53,78,153-234

- bacterial assimilation: 30
- Bardenpho process: 249
- batch culture: 68,85,90-91
- Berl saddles: 281,285,287-288
- biocarbonate: 50,52,215,229-230
- biochemical pathways: 56-58
- biofilm: 43,71,137,153-169
- biofilm controlled: 52,186
- biofilm reactor: 154-169
- biofilm submodel: 198-199
- biofilm surface reaction: 204
- biofilm theory: 22,154-169
- biofloculation: 170
- biofor: 215,229-230
- biological removal: 21-22
- BOD5: 39,183-185,274,313,390,392
- BOD5/TKN ratio: 236
- break through curve: 314,329

- break-point: 21,23,34
- breakpoint chlorination: 295-303
- bromide: 302
- bubble aeration system: 273
- bubble-diffuser: 245
- buffering capacity: 358-360
- buoyant force: 367

- C/N ratio: 127-133
- capital costs: 301
- carbon concentration: 142-144
- carbon oxidation: 29
- carbon source: 229,134-135
- cell residence time: 254
- cell shape: 57
- cell size: 57
- cell-residence time: 239
- cellulose ion exchanger: 334-335
- cellulose resin: 351
- chemical methods: 21
- chemical precipitation: 312,355-392
- chloramine: 295
- chlorination: 21,23,34
- chlorine: 23
- chlorine resistance: 351
- chromatographic techniques: 122
- chromium: 116,118
- classification: 43
- clay: 305
- clinoptilolite: 23,24, 218-232,305,315-318,332,335
- CMF reactor: 379
- cocurrent operation: 324-326
- COD/N ratio: 96
- COD: 40,219,375,390,
- coke plant: 117
- collision efficiency factor: 365
- colloids: 339
- combinations of several limiting factors: 93-94, 147-149
- competition: 97-100
- complete mixed flow: 379-381
- contact stabilization: 248-251
- continuous ion exchange: 320
- copper: 116
- costs: see treatment costs
- counter current operation: 290,327-331
- cross-linking: 307

cyanide: 110,115
 decay coefficient: 240
 decay rate: 105
 definition: 39-40
 denitrification: 11,21-22,28,29,31,43-45,50-52,119-151,216-234
 denitrification efficiency: 130
 denitrification rate: 119-151
 density-temperature relationship: 378
 destabilization: 364,371
 dialysis: 337-339
 diffusion coefficient: 270-27
 diffusion, liquid film: 163
 diffusion resistance: 160,163,204
 dinitrogen oxide: 119-120
 discrete settling: 367
 disinfection: 302
 dissimilation: 122
 dissimilatory reduction: 124
 dry deposition: 10-11
 ecological models: 3
 electrodialysis: 24-25,337-339
 electron transport: 124
 elution liquid: 293
 enzymatic activity: 122
 enzyme inhibition: 104-107
 enzymes: 105,108
 eutrophication: 8,12
 eutrophication models: 15
 extended aeration: 248-251
 facultative organisms: 120
 fertilizer: 8,12-15
 fertilizer industry: 211
 Fick's law: 270
 filamentous organisms: 237,242-244
 first order kinetics: ,17,62-65,379
 fixed bed reactors: 44-45,117,153, 216
 fixed-film reactor: 193
 flocculation tank: 378
 flocculation: 364-367
 flooding point: 284,286
 flotation: 388-389
 fluidized bed: 44,52,153,166
 fluoride: 118
 frame: 350
 free energy: 57-60
 friction factor: 346
 frictional force: 367
 gas transfer: 270-275
 generation time: 57
 glucose-tri-sulfate: 371,375
 grease: 391
 ground water: 119
 growth rate: 66,70
 half order kinetics: 64,160
 half saturation constant:95, see also saturation constant
 health hazard: 3,19
 Henry's constant: 271,277
 herring filleting: 392
 heterotrophic bacteria: 98-100,203
 hollow fibers: 350
 hydraulic load: 174-179,186,188, 192,224-225
 hydraulic retention time: 254
 hydraulic stability: 387
 hydrolysis rate: 347
 incineration: 291
 inhibition models: 109
 inhibition types of: 104
 inhibition: 66,68,85,91-92,104,150-151
 inhibitors: 58,102-118
 ion exchange: 21,23-24,234
 ion exchange: 293, 305-335
 ion-selective: 44
 ionic strength: 262-264
 irrigation: 10
 kinetic constants: 138
 kjeldahl nitrogen: 236
 Lake Tahoe: 267,292
 LD50: 55
 leather industry: 211
 lignosulfonic acid: 376
 limiting factor: 13-14,16
 Lineweaver-Burk Plot: 65,104,107
 linpor: 52
 loading criteria: 237
 Ludzack-Ettinger configuration: 245,247-248

magnesium-ammonium-phosphate: 374,389-390
 mass balance for a biofilm: 165-169
 mass balance of SND: 224
 matrix: 153
 maximum growth rate: 57,62,71,77-80,98,103
 membrane processes: 21,24-26,36,337-339
 methanogenesis: 159,164
 methemoglobinemia: 19
 Michaelis constant: 67
 Michaelis-Menten kinetics: 65-68, see also Monod kinetics
 microaerophilic layer
 microfiltration: 339
 model of activated sludge: 256
 Model of NTF: 177-179
 Monod equation: 97-99
 Monod kinetics: 62-70
 Monod model: 62
 MPN-techniques: 122
 multi-stage operation: 320

 nitrate: 4,8,17,21,35,55,114,120,123-127,149,154,218-232,302,336,392
 nitrification: 21-22,27,29,32,43-45,50-52,55-118
 nitrification-rate: 43,50,71-83,188-191,216-234
 nitrifying trickling filter: 170-192
 nitrite toxicity: 55
 nitrite: 17,23,56,64,66,71,81,92,123-126
 nitro-compounds: 110-11
Nitrobacter winogradskyi: 91
Nitrobacter: 43,55-60,62,66-68,71-73,77-79,90-91,166,203,218-232,253-255
 nitrogen cycle: 4-9
 nitrogen fixation: 11
Nitrosolobus: 55-56
Nitrosomonas: 43,55-60,62,66-68,71-73,77-79,90-91,166,203,218-232,253-255
Nitrosospira: 55-56
Nitrosovibrio: 55-56
Nocardia genus: 244

 operating line: 322-328
 organic loading: 154-157
 orthokinetic flocculation: 366
 osmotic pressure: 25,337-341,348
 oxidation ditch: 251
 oxidation pond: 49
 oxidation rate: 66
 oxygen concentration: 16,84-87 oxygen concentration, influence on nitrification: 84-87
 oxygen consumption: 60
 oxygen profile: 158
 oxygen requirements: 241
 oxygen transfer: 172,244
 oxygen, influence on denitrification: 139
 ozonation: 302

 packed bed reactor: 52
 packed tower: 277
 percolate: 211
 percolating filter: 85
 permeability: 342-345
 permeate: 348-350
 person equivalent: 53
 pH effect in biofilm: 165
 pH influence: 87-93
 pH optimum: 57,87-93
 pH-logC diagrams: 356-360
 phenolic compounds: 110
 phosphorus: 13-15
 physical methods: 21
 plastic filter: 391
 plastic foam particles: 50
 plastic media: 117,170,186,391
 plate: 350
 plug-flow: 236
 polyfloculant: 373-375
 Pomona: 352
 porosity: 217
 potable water: 18
 precipitation: 21,25,37,312,355-392
 predator control: 192
 Pretoria: 292-294
 primary treatment: 46
 proteins: 17,335,371,390
 public health hazard: 19
 pure oxygen activated sludge: 251

Raschig rings: 217,281,285,287-288
 rate of denitrification: 119-151
 RBC: 193-214
 RBC media: 194-195
 recarbonization: 291
 recirculation: 176-179,205
 recovery of proteins: 390
 reductase: 120
 regeneration: 24
 rejection ratio: 343,348
 residence time: 238
 residual chlorine: 296
 resin utilization: 309-310
 retention time: 70-71,222
 reverse osmosis: 24,37
 reverse osmosis: 337-339,341-353
 Reynolds number: 369-371
 river water: 18,81
 rotating contactor: 22,44-45,50,52,153-155,166,193-214
 running costs: 38,301

 safety factor: 100-102,149,254
 saturation constants: 57,70,105,137,181 see also half saturation constant
 secondary treatment: 46
 sedimentation: 366-388
 selectivity coefficient: 308-309,317-318
 selectivity: 22,44,308
 sequential ion exchange: 320
 settling: 366-388
 shock load: 192
 simultaneous nitrification and denitrification: see SND
 sludge age: 235,244
 sludge production: 50,235,240-241,243
 sludge residence time: 248
 SND, mechanism: 231-233
 SND: 28,31,45,52, 207,216-234
 solubility of ammonia: 271-273
 solubility, temperature dependence: 266
 spiral rings: 281
 spiral: 350
 spray tower: 277
 steady state culture: 66
 Stokes law: 369
 stripping tower: 266-268,277-280
 stripping: 21,23,33, 261-294
 submerged filter: 22,24,50,64,85,90-91, 215-234
 sulfate: 159,164
 support material: 153
 surface area: 181-183,186-188,205
 surface of packing: 266
 surface rate: 168-169
 suspended growth: 22,30,32,45,53,71,101
 synthetic ion exchange resin: 306

 temperature coefficient: 83
 temperature influence: 72-80, 141-142,175-177,209-210,347
 terminology: 46-48
 tertiary treatment: 48
 thiobacillus denitrificans: 132
 thiocyanate: 115
 toxic constituents: 95,100,117
 toxicity: 3,12,117,150-152
 transfer coefficient: 273,278-280
 transfer units: 279-284,290
 treatment costs: 38
 trickling filter: 22,45,50-52,64,170-192
 trickling filter medium: 171
 tube settler: 387-388

 ultrafiltration: 337-339
 unit processes: 43,50
 urban run-off: 10
 urea: 17
 utilization rate: 239
 utilization rate: 254

 viscosity-temperature relationship: 377
 volatile acids: 128
 volumetric rate: 168-169

 Warburg respirator: 67
 water recovery: 344
 wet deposition: 10-11
 wetted area: 174
 Windhoek: 303
 Wuhrmann configuration: 245-246

 yield coefficient: 49,57,98,203, 254

zeolite: 44,216

zero order kinetics: 57,62-68, 160-163,168

zeta potential: 363

zone settling: 384-388